

**50 300 Liquid frisket, colourless**  
**50 303 Liquid frisket, coloured**product name:

- Liquid frisket, colourless / liquid frisket, coloured.

contains:

- Synthetic resin dispersion without ammonia.

basic information:

- Masking fluid to be used on relatively smooth, non-greasy and dry supports like, for example, smooth illustration board and similar painting supports to cover up the parts of a picture that are not to be painted over.

characteristics:

- Colourless or blue tinted
- transparent
- without ammonia
- odourless.

handling:

- Shake well before use.
- *Liquid frisket, colourless / liquid frisket, coloured* is ready to use and can apply using a cotton bud, a chopstick, nib or a quill. (Don't use expensive brushes!)
- The product is dilutable with water, but dries very quickly into a rubbery-type transparent film that does not dissolve in water. (With water diluted product may be penetrate deeper into the ground and it is possible that product will be worse removed!)
- Please clean tools as soon as possible with water or water and soap.
- Close the top tightly as soon as possible after use.
- After the masking fluid is completely dry, the masked picture areas can be painted over using water-colours, gouache colours or AERO COLOR® Professional. (The drying process takes between a few minutes and more than an hour depending on the thickness of the coat!)
- After this coat of paint has dried properly too, the dried rubbery-type film of the masking fluid can be removed by careful rubbing with a dry and non-greasy finger (please do not pull off!).
- The masking film should not be left on the support for longer than two days and must be completely removed; otherwise there is a risk of yellowing of the support!
- Very soft, weakly grounded textured paper types like e.g. rag paper or torchon paper are not suitable for masking techniques.
- Close immediately after use.
- Store in a cool and dry place.
- Protect from frost.
- Individual pre-tests are required (see footer).

product labeling:

- Please refer to the individual safety data sheet on our website [www.schmincke.de](http://www.schmincke.de).

DrK/ 01.07.2014

H. Schmincke & Co. GmbH & Co. KG · Otto-Hahn-Str. 2 · D - 40699 Erkrath ·  
Tel.: +49-211-2509-0 · [www.schmincke.de](http://www.schmincke.de) · [info@schmincke.de](mailto:info@schmincke.de)



The described product characteristics and example applications have been tested at the Schmincke laboratory. The information is based on the technical knowledge and experience which are presently available to us. In view of the diversity of applications with regard to painting techniques, materials and working conditions and the numerous possible influencing factors, the information refers to general areas of application. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application; use of the products is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept any liability for damage arising in connection with the use of our products.